

## smart 3 U – The System that Grows with Your Needs

proxSafe®

Where is the digital camera? Who has been using the company car? When was the technician in the building? proxSafe is the intelligent management system for keys and valuables which provides answers to your daily 'key questions'. Contactless RFID keyTag technology provides reassuring reliability. The proxSafe family is modular, expandable and network ready.

### smart 3 U

proxSafe smart 3 U is your first choice if a small number of keys should be securely stored and only issued to authorized persons. Users and keyTags are identified contactless and all transactions are automatically recorded. Any size from 8 to 32 slots can be realized. The proxSafe smart3U is equipped with a basic version of Terminal, Software and power supply. The system is limited to 32 keyTags and 32 users and has a USB 2.0 interface or an optional Ethernet plug for PC connection. proxSafe smart 3 U consists of a robust steel cabinet in a discreet color. The keyPanels with various slot densities are site-assembled into the cabinet. The door is constructed of sheet steel with a clear window pane. Every proxSafe housing contains tamper monitoring and 4 dry outputs for numerous alarms which are detected by the powerful Commander and Terminal software.

The generous resident memory of the user terminal allows operation even if the network fails and a back-up battery takes over in case of power failures. An emergency key is provided in order to allow manual access to the cabinets and keyTags if necessary.

The keyTags and slots are designed for rugged operation. Using RFID-Technology, there are no electrical contacts on the keyTags. Dirt, corrosion or wear by daily operation are impossible. proxSafe keyTags and the according slots require no cleaning or maintenance.

### Your benefits at a glance:

- **Contactless – No corrosion, No Wear**
- **Maintenance-Free Operation**
- **Operates Standalone or Remote Controlled**
- **Available in Various Slot Counts and Densities**
- **Compatible to the Full Range of proxSafe Components**



### Technical Data

#### Dimensions:

mm (inch) W x H x D 609 x 282 x 210 (24 x 11 x 8)

#### Weight:

kg (lbs) 14.2 (31.3)

#### Housing Material:

sheet steel, powder-coated

#### Colour:

similar to RAL 9006

#### Operating Temperature:

°C (°F) +5...+50 (+41...+122)

#### Relative Humidity:

% 5...95, non-condensing

#### Power Requirement:

13.8 VDC / max. 2 A per housing

#### Frequency:

kHz 125

#### Available Keyslots:

Double Density: 1 x 32 DD = 32 Slots

Single Density: 1 x 16 SD = 16 Slots

Single Density: 1 x 8 SD = 8 Slots